



ABC Dry Chemical

Manufactured and Tested to
ANSI/UL Standards

Amerex is an ISO-9001:2000
Registered Firm

- ★ Dependable Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and less costly to maintain and service
- ★ U/L & U.S. Coast Guard Listed
- ★ Bar Coded Labels

(Temperature Range -65°F to 120°F)

Note: All extinguishers are U.S. Coast Guard approved with bracket listed on U.L. label.

Stored Pressure



ABC or Multi-Purpose extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 350°F and coats surface to which it is applied. It smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.

Available in Wheeled and Stationary extinguishers.

6 YEAR WARRANTY

SPECIFICATIONS	ABC Dry Chemical										
VALVES	ALUMINUM						BRASS, CHROME PLATED				
Size & Capacity (lbs.)	2 ½	5	5	6	10 Tall	20	5	6	10 Short	10 Tall	20
Application	Nozzle	Hose and Nozzle					Hose and Nozzle				
Model Number	B417 / B417T	B500 / B500T	B402 / B402T	B443	B456	A411	B424	B461	419	B441	423
U/L Rating	1A:10B:C	2A:10B:C	3A:40B:C	3A:40B:C	4A:80B:C	20A:120B:C	2A:10B:C	3A:40B:C	4A:80B:C	4A:80B:C	20A:120B:C
Shipping Wt. (lbs.)	5¼ / 5½	9¼ / 9½	9¼ / 9½	12¾	18	38	10½	13¾	19	19	39
Height (in.)	15½	15¼	15¼	16	20	23¾	15½	16¼	17 5/8	20½	24
Width (in.)	5¼	7¼	7¼	7¼	7¼	10¼	8	8½	9½	8¾	10¼
Depth (Diam. - in.)	3	4¼	4 ¼	5	5	7	4¼	5	6	5	7
Range (ft.)	9 - 15	12 - 18	12 - 18	15 - 21	15 - 21	15 - 21	12 - 18	15 - 21	15 - 21	15 - 21	15 - 21
Discharge Time (Sec.)	10	14	14	14½	20	30	14	14	22	20	30
Available with Chrome Plated Cylinder	YES	YES	YES		YES					YES	
F. M. Approved	YES	YES		YES	YES	YES		YES	YES	YES	YES
Standard Bracket	Wall / Vehicle-Marine			Wall			Wall				